




# GOMTEX<sup>®</sup> ZERO SNEAKING



## Performance


- Extension almost 0 The only hose on the market without instability.
- Excellent resistance to abrasion and intensive use by professionals.
- Highly resistant to oil, gasoline and a wide range of chemicals.
- Very resistant to both contact and radiant heat.
- Light and flexible hose even at low temperatures (-15°C) Easy to handle and roll up.
- Highly resistant to breakage thanks to the specially-made textile.
- No maintenance or drying necessary.
- Available for compliance with various international certifications.

## Uses

- Agriculture.
- Water transfer, bypass.
- Coating of cables and other piping.
- Compressed air applications Pump exitway.
- Construction and civil works.
- Fire-fighting and industrial use.
- Refineries.
- Marine use on ships and platforms.
- Military use.
- Airports.
- Forestry.



# GOMTEX® ZERO SNEAKING



## Construction

### Interior and exterior layer:

Specially-formulated nitrile rubber, extruded through the circular fabric. Minimal flow loss thanks to its smooth interior wall. High thermal resistance.

### Reinforced middle textile:

Circular weaved outer layer made from high tenacity polyester thread. No defects (broken threads, knots, etc.)

## Tecnical characteristics

DIAMETER		WEIGHT	THICKNESS	WORKING PRESSURE	BREAKAGE PRESSURE
INCHES	MM.	GR/M.	MM.	BARS	BARS
6"	155	1.650	4,00	14	>50
8"	205	3.100	4,30	12	>40
10"	257	4.000	4,50	12	>40